

Be smart. Modernize your office.

The ECOSYS MA4000wifx reduces wait times for busy organizations, and offers increased memory capacity as well as high processor speed.



ECOSYS MA4000wifx

A4 B&W multifunctional printer

Up to 42 pages per minute

Print, copy, scan, and fax

Optional HyPAS™ solution platform

ECOSYS MA4000wifx

BASIC SPECIFICATIONS

Configuration: B&W MFP - Print / Scan / Copy / Fax
Pages per Minute: Letter: 42 ppm; Legal: 34 ppm; A4: 40 ppm
Duplex Print Speed: Letter 21 ppm; Legal 17 ppm; A4 20 ppm
Display: 4.3" Color Touch Screen Control Panel (TSI)
Warm Up Time: 29 Seconds or Less (Power On)
First Page Out Time:
Copy: 6.4 Seconds or Less
Print: 6.4 Seconds or Less
Resolution: 300dpi, 600dpi, up to Fine1200
Memory: 2GB
Duplex: Standard Stackless Duplex Supports Statement to Legal (5.5" x 8.5" - 8.5" x 14"), 16 lb. Bond - 90 lb. Index (60 - 163gsm)
Dimensions / Weight: 18.7" W x 16.2" D x 17.2" H / 43 lbs
Monthly Print Volume: 80,000 Pages per Month

POWER CONSUMPTION

Electrical Requirements: 120V, 60Hz, 8.9A; 220-240V, 50/60Hz, 4.1A
Typical Electricity Consumption (TEC):
120V: 0.36 kWh/week; 220-240V 0.35 kWh/week
Maximum (including Options): 120V: 1,135 W; 220-240V: 1,107 W
Copy/Printing: 120V: 577.9/577.9 W; 220-240V: 574.4/574.4 W
Ready Mode: 120V: 11.4W; 220-240V: 11.8W
Sleep Mode: 120V: 0.4W; 220-240V: 0.4 W
Power Off: 120V: 0.1 W; 220-240V: 0.1 W

PRINTER SPECIFICATIONS

Standard Controller: ARM Cortex A53 single 1.0GHz + ARM Cortex-M3 100MHz
PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL-5e), KPDL3 (PostScript3 compatible), PDF w/KPDL3 setting, XPS / Open XPS
Fonts: Outline: 93 Fonts (PCL 6/KPDL3), 4 Calibri, 4 Cambria, Bitmap: 1 Font, 79 Outline Fonts
Barcodes: 1 Dimensional: 45 Type; 2 Dimensional: PDF417 1 Type
Windows OS Compatibility: Windows 10 (32/64), Windows 11 (64), Windows Server 2016, 2019, 2022
MAC OS Compatibility: MAC OS X 10.9 or Greater
Linux Printer Driver: Ubuntu 20.04 or higher, Debian 11 or higher, OpenSUSE 15.5 or higher, Fedora 39 or higher, CentOS Stream 9 or higher
Chrome OS: Version 118 or Higher
Interfaces: 10 BASE-T/100 BASE-T/1000 BASE-T, USB 2.0, 1 USB Host
Mobile Printing: Apple AirPrint®, Mopria®, KYOCERA Mobile Print, KYOCERA MyPanel, KYOCERA Android Print Service Plugin

Solutions: HyPAS¹ - Kyocera Cloud Print and Scan, Multi Crop Scan, KYOCERA Net Manager Embedded Terminal
Network Print and Supported Protocols: TCP/IP V4/V6, NetBEUI, FTPS, LPR, Port9100, IPPS, WSD, SMTP, SNMP, SIEM
Drivers: KX Driver, PCL Uni Driver, KPDL Uni Driver, TWAIN Driver (Network & USB), WIA Driver (Network & USB), MAC Driver, Linux Driver, ChromeOS Driver, Network Fax Driver
Utilities: KYOCERA Quick Scan, KYOCERA Print Center, KYOCERA Cloud Access, Scan-to-Folder Setup Tool for SMB, KYOCERA Net Direct Print, KYOCERA Net Viewer, KYOCERA Device Manager, KYOCERA Quick Network Setup, KYOCERA Fleet Services
²**SDHC or SD required for:** Private Print, Quick Copy Box, Job Box, Proof & Hold, and Job Storage

SECURITY

Standard: Local & Network Authentication, IPsec, HTTPS, SNMPv3, IPPS, POP over TLS, FTPS and LDAPS, SMTP over TLS

SCAN SPECIFICATIONS

Scan Type: Color, Grayscale, B&W
Scan Methods: PC (SMB Version 3.0), E-mail (SMTP), USB, FTP, FTPS WSD (Network), TWAIN Source (Network & USB), WIA (Network & USB)
Scan Resolution: 200/300/400/600 dpi and up to 1200 dpi (TWAIN)
Scanning Functions: Continuous Scan, Blank Page Skip, DP Auto Crop, WIAScan, ChromeOS (Scan)
File Formats: TIFF (MMR/JPEG compression), JPEG, XPS, Open XPS, PDF (High compression), PDF/A-1, PDF/A-2, Encrypted PDF
Original Size: Min/Max: Statement to Legal (5.5" x 8.5" - 8.5" x 14")

COPY SPECIFICATIONS

Image Mode: Text, Photo, Text & Photo, Light Text/Fine Line
Copy Quantity: 1- 999 / Auto Reset to 1
Job Management: 300 Address Book Records, 11 One-Touch Keys, 4 Program Keys
Magnification / Zoom: Auto Zoom, Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25% - 400% in 1% Step Increments
Additional Copy Features: Auto Paper Select (APS), Background Density Adjustment, Auto Zoom, Auto Duplex, ID Card Copy, Quiet Mode

FAX SPECIFICATIONS

Type / Data Compression: G3 Fax / MMR, MR, MH, JBIG
Transmission Speed / Modem Speed: 3 seconds or less (JBIG) / 33.6Kbps

Fax Memory:

3.5 MB
Fax Functions: Fax Direct Tx, Fax Memory Tx, Scheduled transmission, Fax Polling, Forward Fax, Group Fax, Dial-in/out (LS Model), Number Display Mode, Fax Dedicated Paper Source, Network Fax Tx & RX Group Fax, Fax Dedicated Paper Source, Network Fax Tx & RX

DOCUMENT PROCESSOR

Type / Capacity: Dual Scan Document Processor (DSDP) / 50 Sheets (80gsm)
Acceptable Originals: Statement to Legal (5.5" x 8.5" - 8.5" x 14")
Acceptable Weights: Simplex / Duplex: 13 - 32 lb Bond (50 - 120gsm)

PAPER SUPPLY

Standard / Maximum Paper Capacity: 350 Sheets / 850 Sheets
Standard / Maximum Paper Sources: 2 / 4 Including Multipurpose Tray
Paper Output Capacity: 150 Sheets
Paper Size: Standard and MPT: Statement to Legal (5.5" x 8.5" - 8.5" x 14"), Custom
Paper Weight: Drawer 16 lb. Bond - 90 lb. Index (60 - 163gsm); MPT: 16 lb. Bond - 120 lb. Index (60 - 220gsm)
Input Materials: Plain Paper, Bond Paper, Recycled Paper, Thin Paper, Thick Paper; MPT: Labels, OHP, Envelopes

PAPER HANDLING OPTIONS

PF-1100: Paper Feed Cassette 250-sheet Paper Tray (total of 2 additional trays can be added)
Paper Size: Statement to Legal (5.5" x 8.5" - 8.5" x 14")
Paper Weight: 16 lb Bond - 90lb Index (60-163gsm)
Input Materials: Plain Paper, Bond Paper, Recycled Paper; MPT: Thick paper, Thin paper, Labels, Transparency, Envelopes
Dimensions / Weight: 14.8" W x 15.5" D x 3.9" H / 6.4 lbs

ADDITIONAL OPTIONS

Print Management: ThinPrint (UG-33)
Security: Card Authentication Kit (B)
SDHC or SD Card: 16 / 32 GB
UG-50: TPM (Trusted Platform Module)

NOTE:

¹HyPAS Requires Optional SD Card
²SDHC or SD required for: Private Print, Quick Copy Box, Job Box, Proof & Hold, and Job Storage

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. ECOSYS, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America
225 Sand Road, PO Box 40008
Fairfield, New Jersey 07004-0008, USA
Tel: 973-808-8444



Kyocera Document Solutions Partner



kyoceradocumentsolutions.us

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
©2024 KYOCERA Document Solutions America, Inc.